



SILTECH CORPORATION
225 Wicksteed Avenue
Toronto, Ontario, Canada, M4H 1G5
(416)424-4567 (Tel) (416)424-3158 (Fax)

TECHNICAL DATA SHEET

Siltech[®] C-261

Description

Siltech[®] C-261 is a modified silicone glycol copolymer diluted in butyl acetate. It provides leveling, substrate wetting and mar and abrasion resistance to solvent based paints, inks and coatings.

Typical Properties

Appearance	Clear Liquid
Colour, Gardner, maximum	4 max
Active Content %	15
Viscosity at 25°C, cps	3
Specific Gravity at 25°C	0.910
Functionality	Hydroxyl
Solvents	Butyl acetate

Application & Uses

Siltech[®] C-261 is used as an additive for solvent based systems. It improves leveling, substrate wetting, mar and abrasion resistance. It also prevents floating and cratering.

It is recommended that **Siltech[®] C-261** be used between 0.1-1.0% weight percent based on the total formulation. It can be added at any stage during the process.

Siltech[®] C-261 is effective at very low levels and shows excellent compatibilities in solvent-based systems.

Shelf Life

When stored in the original, unopened containers between 10 and 40°C, **Siltech[®] C-261** has a shelf life of 36 months from date of manufacture.

Packaging

Siltech[®] C-261 is supplied in 20kg pails and 200kg drums.

Legal Disclaimer

Siltech Corporation believes that the information in this technical data sheet is an accurate description of the typical uses of the product. Siltech Corporation, however, disclaims any liability for incidental or consequential damages, which may result from the use of the product that are beyond its control. Therefore, it is the user's responsibility to thoroughly test the product in their particular application to determine its performance, efficacy and safety. Nothing contained herein is to be considered as permission or a recommendation to infringe any patent or any other intellectual property right.

SILTECH[®] is a registered trademark of Siltech Corporation, Toronto, Ontario, Canada.

October 2008