



# SILTECH CORP.

## Safety Data Sheet

Prepared in accordance with GHS standard  
& Annex II - EC regulation 1907/2006 and amendments

Siltech C-174  
SDS No: 2860.2

Last Revision Date: June 16, 2015

### SECTION 1. IDENTIFICATION

**Material Identification:** Siltech C-174

**Company Identification:** Siltech Corp.

**Chemical Name:** Polydimethylsiloxane copolymer in xylene & isobutanol

225 Wicksteed Avenue

**Chemical Classification:** Silicone

Toronto, Ontario

**CAS #:** 68937-55-3 / 1330-20-7 / 78-83-1

Canada

M4H 1G5

(416) 424-4567

**Recommended Product Usage**

Additive

**CANUTEC 24-HOUR EMERGENCY RESPONSE TELEPHONE NUMBER: (613) 996-6666**

USE IN CASE OF A DANGEROUS GOODS EMERGENCY

### SECTION 2. HAZARD(S) IDENTIFICATION

**HAZARD CLASSIFICATION:**

Flammable liquids	Category 3	
Acute toxicity	Category 4	Dermal
Acute toxicity	Category 4	Inhalation (drowsiness and dizziness, respiratory irritation)
Serious eye damage	Category 1	
Skin irritation	Category 2	

**GHS LABEL ELEMENTS** (including precautionary statements):

Symbol :



Signal Word:

Warning

Hazard Risk Statement:

- H226: Flammable liquid and vapour
- H312: Harmful in contact with skin
- H332: Harmful if inhaled
- H318: Causes serious eye damage
- H315: Causes skin irritation

Precautionary Statement:

Prevention:

- P210: Keep container tightly closed and away from ignition sources such as heat, sparks and open flame. NO SMOKING.
- P264: Wash hands thoroughly after handling.
- P271: Use in well ventilated area.
- P280: Wear protective gloves/ protective clothing/eye protection/face protection.

Response:

- P351 + P313: IF IN EYES: Rinse cautiously with water for several minutes.
- P302 + P350: IF ON SKIN: Wash with plenty of soap and water.

Storage:

- P403 + P235: Store in well-ventilated place. Keep cool.

Disposal:

- P501: Dispose of contents/container in accordance with local / regional / national / international regulations.

**OTHER HAZARD** (risk not included in classification):

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u>	<u>Common Name or Synonym</u>	<u>CAS No.</u>	<u>EINECS/ ELINCS No.</u>	<u>% (w/w)</u>	<u>GHS Classification</u>	<u>Classification according to Directive 67-548/EEC</u>
Xylene	dimethylbenzene	1330-20-7	215-535-7	30 - 50	Flammable liquids: Category 3 Acute toxicity $\delta$ dermal : Category 4 Acute toxicity $\delta$ inhalation : Category 4 Skin irritation: Category 2	Xn R10 R20/21 R38
2-methylpropan-1-ol	isobutanol	78-83-1	201-148-0	5 - 15	Flammable liquids: Category 3 Specific target organ toxicity (single exposure): Category 3 Skin irritation: Category 2 Serious eye damage: Category 1	Xi R10 R37/38 R41, R67

Other ingredients not listed in this section are non-hazardous or business confidential.

### SECTION 4. FIRST AID MEASURES

**Eyes:** Immediately flush with water for 15 minutes. Obtain medical attention if irritation occurs.

**Skin:** Remove contaminated clothing and wash with soap and water. Obtain medical attention if irritation occurs.

**Inhalation:** If first aid is required move victim to fresh air. Obtain medical attention if irritation occurs.

**Ingestion:** Do not induce vomiting and obtain medical attention immediately.

### SECTION 5. FIRE FIGHTING MEASURES

**Suitable Extinguishing Media:** Carbon dioxide, dry powder, foam. Water can be used to cool fire exposed containers.

**Unsuitable Extinguishing Media:** None known.

**Specific Hazards Arising from the Chemical:** Silicon Dioxide. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

**Special Protective Actions for Fire-Fighters:** Self-contained breathing apparatus and protective clothing should be worn in fighting fires involving chemicals. Use water spray to cool fire exposed containers.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions and Protective Equipment:** Avoid eye and skin contact. Use personal protective equipment.

**Environmental Precautions:** Prevent from entering drains or water sources.

**Containment/Clean up:** Collect for disposal. Clean up remaining materials from spill with suitable absorbent. For large spills provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean area as appropriate since some silicone material, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents.

### SECTION 7. HANDLING AND STORAGE

**Handling Precautions:** Avoid eye and skin contact. Do not take internally. Use with adequate ventilation. Wash after handling. Exercise good industrial hygiene practice.

**Storage Conditions:** Keep container tightly closed and away from heat, sparks, and flame. Ground all equipment. Static electricity will accumulate and may ignite vapours.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### OCCUPATIONAL EXPOSURE LIMIT VALUES / BIOLOGICAL LIMIT VALUES:

#### Industrial Hygiene Standards

<u>Ingredient</u>	<u>CAS No.</u>	<u>Exposure Limit</u>
Xylene	1330-20-7	ACGIH TLV-TWA: 100 ppm / OSHA PEL – TWA: 100 ppm
Isobutanol	78-83-1	ACGIH TLV-TWA: 100 ppm / OSHA PEL – TWA: 100 ppm

#### ENGINEERING CONTROLS:

Local Ventilation: Recommended.  
General ventilation: Required.

#### PERSONAL PROTECTIVE EQUIPMENT:

Respiratory protection: In the case of vapour formation use a respirator with an approved filter.  
Hand protection: Chemical protective gloves are recommended (Fluoro carbon rubber, permeation time  $\geq$  8hrs).  
Eye protection: Use proper protection - safety glasses as a minimum.  
Skin protection: Impervious clothing.  
Hygiene measures: Observe good industrial hygiene practices. Wash after handling.

**Note:** These precautions are for room temperature handling. Use at elevated temperatures or aerosol spray applications may require added precautions.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

<u>Appearance:</u>	Clear liquid	<u>Viscosity@25°C:</u>	10 - 50 cps
<u>Colour:</u>	Colourless to Yellow	<u>Melting/Freezing Point:</u>	Not determined
<u>Odour:</u>	Characteristic	<u>Initial Boiling Point:</u>	>100°C @ 760 mmHg
<u>Odour Threshold:</u>	Not determined	<u>Boiling Range:</u>	Not determined
<u>Flash Point:</u>	27°C (Pensky-Martens closed cup)	<u>Explosive Properties:</u>	No
<u>Flammability:</u>	Not determined	<u>Vapour Pressure @25°C:</u>	Not determined
<u>Flammability Limits:</u>	Xylene (lower: 1% upper: 7%)	<u>Vapour Density</u>	Not determined
<u>Auto-ignition Temperature:</u>	465°C	<u>Partition Coefficient</u>	Not determined
<u>Decomposition Temperature:</u>	Not determined	<u>pH:</u>	Not determined
<u>Specific Gravity @25°C:</u>	Not determined	<u>Oxidising Properties:</u>	No
<u>Solubility in Water:</u>	Insoluble	<u>Evaporation Rate:</u>	Not determined

## SECTION 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable.

**Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.

**Conditions to Avoid:** None known.

**Incompatible Materials:** Strong oxidizing material can cause a reaction.

**Hazardous Decomposition Products:** The following decomposition products may form during fire or at very high temperatures: Carbon Oxides, Silicon dioxide, Formaldehyde, and traces of incompletely burned carbon compounds.

## SECTION 11. TOXICOLOGICAL INFORMATION

### LIKELY ROUTES OF EXPOSURE:

<b>Respiratory:</b>	Exposure is expected.
<b>Oral:</b>	Exposure is expected.
<b>Eye, Skin:</b>	Exposure is expected.

### INFORMATION ON THE HEALTH HAZARDS:

#### **Acute Toxicity:**

<b>Eyes:</b>	Direct contact may cause temporary redness and discomfort.
<b>Skin:</b>	Xylene: (LD50 Dermal ó rabbit ó 1700 mg/kg)
<b>Inhalation:</b>	Xylene: (LC50 Dermal ó rat ó 21.7 mg/l ó 4h)
<b>Ingestion:</b>	Xylene: (LD50 Dermal ó rat ó 4300 mg/kg)

#### **Chronic Toxicity:**

<b>Skin:</b>	Xylene: may cause degreasing or inflammation to skin..
<b>Inhalation:</b>	No known applicable information.
<b>Ingestion:</b>	Repeated ingestion or swallowing large amounts may injure internally.
<b>Other Health Hazard</b>	No known applicable information.

**Skin Corrosion/Irritation:** No known applicable information.

**Serious Eye Damage/Irritation:** No known applicable information.

**Respiratory Sensitization:** No known applicable information.

**Skin Sensitization:** No known applicable information.

**Carcinogenicity:** No known applicable information.

**Germ Cell Mutagenicity:** No known applicable information.

**Reproductive Toxicity:** No known applicable information.

**Specific Target Organ:** No known applicable information.  
(Systemic Toxicity – Single exposure)

**Specific Target Organ:** No known applicable information.  
(Systemic Toxicity – Repeated exposure)

**Aspiration Hazard:** No known applicable information.

## SECTION 12. ECOLOGICAL INFORMATION

### ECOTOXICITY:

#### Environmental Effects

Xylene: (LC50 Fish ó 15.7 mg/l ó 96 hrs)

Xylene: (LC50 Crustaceans ó 8.5 mg/l ó 48 hrs)

### PERSISTENCE AND DEGRADABILITY:

#### Degradation:

In soil, siloxanes are degraded. The organic solvent is biodegradable.

#### Environmental Fate and Distribution:

Siloxanes are removed from water by sedimentation sewage or binding to sludge.  
Organic solvents may evaporate into atmosphere and degrade.

### BIOACCUMULATIVE POTENTIAL:

#### Bioaccumulation:

No bioaccumulation potential.

### MOBILITY IN SOIL:

None known.

### OTHER ADVERSE EFFECTS:

None known.

## SECTION 13. DISPOSAL CONSIDERATIONS

**Product Disposal:** Do not dispose of waste into sewer. Dispose of in accordance with local regulations.

**Packaging Disposal:** Dispose of in accordance with local regulations.

## SECTION 14. TRANSPORTATION INFORMATION

### AIR TRANSPORT (IATA):

**UN No.:** 1993  
**Proper Shipping Name:** Flammable Liquid, n.o.s. (Xylene / Isobutanol Solution)  
**Class:** 3  
**Packing group:** III  
**Labels:** Flammable Liquid

### SEA TRANSPORT (IMDG):

**UN No.:** 1993  
**Proper Shipping Name:** FLAMMABLE LIQUID, N.O.S. (XYLENE / ISOBUTANOL SOLUTION)  
**Class:** 3  
**Packing group:** III  
**Emergency Schedule:** F-E  
**(EmS):** S-E  
**Labels:** Flammable liquid

### ROAD / RAIL (US DOT/CANADA TDG/ADR/RID):

**UN No.:** 1993  
**Proper Shipping Name:** Flammable Liquid, n.o.s. (Xylene / Isobutanol Solution)  
**Class:** 3  
**Packing group:** III  
**Labels:** 3

## SECTION 15. REGULATORY INFORMATION

### CHEMICAL INVENTORIES:

<b>TSCA:</b>	All ingredients are on the inventory.
<b>DSL:</b>	All ingredients are on the inventory.
<b>EINECS:</b>	All ingredients are on or exempted from the inventory.
<b>AICS:</b>	All ingredients are on the inventory.
<b>IECSC:</b>	All ingredients are on the inventory.
<b>MITI:</b>	All ingredients are on the inventory.
<b>KECL:</b>	All ingredients are on the inventory.
<b>NZIoC:</b>	All ingredients are on the inventory.
<b>CSNN:</b>	All ingredients are on the inventory.
<b>PICCS:</b>	All ingredients are on the inventory.

### CANADA

This product has been classified in accordance with the hazard criteria of the CPR, and this MSDS contains all the information required by the CPR.

**WHMIS Classification:** CLASS B Division 2 | CLASS D Division 1B | CLASS D Division 2A | CLASS D Division 2B

### USA

#### **EPA SARA Title III Chemical Listings:**

Section 302 Extremely Hazardous Substances (40 CFR 355):	<b>None</b>
Section 304 CERCLA Hazardous Substances (40 CFR 302):	<b>None</b>
Section 311/312 Hazard Class (40 CFR 370):	Acute: <b>YES</b> ; Chronic: <b>YES</b> ; Fire: <b>YES</b> ; Pressure: <b>No</b> ; Reactive: <b>No</b>
Section 313 Toxic Chemicals (40 CFR 372):	<b>Xylenes (CAS# 1330-20-7) 30 - 50 %</b>

### Supplemental State Compliance Information

#### **California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm: **None known.**

#### **Massachusetts / New Jersey / Pennsylvania**

Xylenes (CAS#1330-20-7) 30 - 50%  
Isobutanol (CAS# 78-83-1) 5 to 15 %

HMIS	
<b>H</b>	2
<b>F</b>	3
<b>R</b>	0



### EEC

#### **Labelling according to EEC Directive**

**Symbols:** Xn (Harmful) | Xi (Irritant)

**R-phrases:** R10 (Flammable) | R20/21 (Harmful by inhalation and in contact with skin) | R37/38 (Irritating to respiratory system and skin) | R38 (Irritating to skin) | R41 (Risk of serious damage to eyes) | R67 (Vapours may cause drowsiness and dizziness)

**S-phrases:** S24 (Avoid contact with skin) | S26 (In case of contact with eyes, rinse immediately with plenty of water and seek medical advice)

### GERMANY

**Wassergefährdungsklasse** (water hazard class) : WGK 2

## SECTION 16. OTHER INFORMATION

The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. This data is offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

**SDS prepared by:** Raj Moonsammy  
**Address:** Siltech Corp  
225 Wicksteed Avenue  
Toronto, Ontario, Canada M4H 1G5  
**Telephone:** (416) 424-4567  
  
**First Issuing Date:** December 04, 2012  
**Revision No.:** 2  
**Latest Revision Date:** June 16, 2015

*This is the last page.*